



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'INFINITY.3'

\$ man INFINITY.3

INFINITY(3) Linux Programmer's Manual INFINITY(3)

NAME

INFINITY, NAN, HUGE_VAL, HUGE_VALF, HUGE_VALL - floating-point constants

SYNOPSIS

```
#define _ISOC99_SOURCE    /* See feature_test_macros(7) */  
  
#include <math.h>  
  
INFINITY  
  
NAN  
  
HUGE_VAL  
  
HUGE_VALF  
  
HUGE_VALL
```

DESCRIPTION

The macro INFINITY expands to a float constant representing positive infinity.

The macro NAN expands to a float constant representing a quiet NaN (when supported). A quiet NaN is a NaN ("not-a-number") that does not raise exceptions when it is used in arithmetic. The opposite is a signaling NaN. See IEC 60559:1989.

The macros HUGE_VAL, HUGE_VALF, HUGE_VALL expand to constants of types double, float, and long double, respectively, that represent a large positive value, possibly positive infinity.

CONFORMING TO

C99.

On a glibc system, the macro HUGE_VAL is always available. Availability of the NAN macro can be tested using #ifdef NAN, and similarly for INFINITY, HUGE_VALF, HUGE_VALL. They

will be defined by `<math.h>` if `_ISOC99_SOURCE` or `_GNU_SOURCE` is defined, or `__STDC_VER?`
`SION__` is defined and has a value not less than 199901L.

SEE ALSO

`fpclassify(3)`, `math_error(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2020-12-21

INFINITY(3)