



Linux Ubuntu 22.4.5 Manual Pages on command 'Lintian::Processable::Orig.3'

\$ man Lintian::Processable::Orig.3

Lintian::Processable::Orig(3) Debian Package Checker Lintian::Processable::Orig(3)

NAME

Lintian::Processable::Orig - access to collected data about the upstream (orig) sources

SYNOPSIS

```
use Lintian::Processable;  
  
my $processable = Lintian::Processable::Binary->new;
```

DESCRIPTION

Lintian::Processable::Orig provides an interface to collected data about the upstream (orig) sources.

INSTANCE METHODS

orig

Returns the index for orig.tar.gz.

orig_index (FILE)

Like "index" except orig_index is based on the "orig tarballs" of the source packages.

For native packages "index" and "orig_index" are generally identical.

NB: If sorted_index includes a debian packaging, it is was contained in upstream part of the source package (or the package is native).

Needs-Info requirements for using orig_index: src-orig-index

sorted_orig_index

orig_index_resolved_path(PATH)

Resolve PATH (relative to the root of the package) and return the entry denoting the resolved path.

The resolution is done using resolve_path.

NB: If orig_index_resolved_path includes a debian packaging, it is was contained in upstream part of the source package (or the package is native).

Needs-Info requirements for using orig_index_resolved_path: Same as orig_index

AUTHOR

Originally written by Felix Lechner <felix.lechner@lease-up.com> for Lintian.

SEE ALSO

lintian(1)

Lintian v2.62.0ubuntu2.2

2022-11-09

Lintian::Processable::Orig(3)