



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'XtAppAddInput.3'

\$ man XtAppAddInput.3

XtAppAddInput(3) XT FUNCTIONS XtAppAddInput(3)

NAME

XtAppAddInput, XtRemoveInput - register and remove an input source

SYNTAX

```
#include <X11/Intrinsic.h>
```

```
XtInputId XtAppAddInput(XtAppContext app_context, int source, XtPointer condition, XtIn?  
putCallbackProc proc, XtPointer client_data);
```

```
void XtRemoveInput(XtInputId id);
```

ARGUMENTS

app_context

Specifies the application context that identifies the application.

client_data

Specifies the argument that is to be passed to the specified procedure when in?
put is available.

condition Specifies the mask that indicates a read, write, or exception condition or some
operating system dependent condition.

id Specifies the ID returned from the corresponding XtAppAddInput call.

proc Specifies the procedure that is to be called when input is available.

source Specifies the source file descriptor on a UNIX-based system or other operating system dependent device specification.

DESCRIPTION

The XtAppAddInput function registers with the Intrinsics read routine a new source of events, which is usually file input but can also be file output. Note that file should be loosely interpreted to mean any sink or source of data. XtAppAddInput also specifies the conditions under which the source can generate events. When input is pending on this source, the callback procedure is called.

The legal values for the condition argument are operating-system dependent. On a UNIX-based system, the condition is some union of XtInputReadMask, XtInputWriteMask, and XtInputExceptMask. The XtRemoveInput function causes the Intrinsics read routine to stop watching for input from the input source.

SEE ALSO

XtAppAddTimeOut(3), XtAppAddSignal(3)

X Toolkit Intrinsics - C Language Interface

Xlib - C Language X Interface

BUGS

In ANSI C it is necessary to cast the condition to an XtPointer, e.g.:

```
XtAppAddInput(app_context,  
             source,  
             (XtPointer) (XtInputReadMask | XtInputWriteMask),  
             proc,  
             client_data);
```

