



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtCallActionProc.3'***

***\$ man XtCallActionProc.3***

XtCallActionProc(3)                      XT FUNCTIONS                      XtCallActionProc(3)

NAME

XtCallActionProc - invoke an action procedure directly

SYNTAX

```
#include <X11/Intrinsic.h>

void XtCallActionProc(Widget widget, const char *action, XEvent *event, String *params,
    Cardinal num_params);
```

ARGUMENTS

- widget    Specifies the widget in which the action is to be invoked. Must be of class core of any subclass thereof.
- action    Specifies the name of the action routine.
- event    Specifies the contents of the event passed to the action routine.
- params    Specifies the contents of the params passed to the action routine.
- num\_params    Specifies the num of entries in params.

DESCRIPTION

XtCallActionProc searches for the named action routine in the same manner and order as translation tables are bound. If found, the action routine is invoked with the specified widget, event pointer, and parameters. It is the responsibility of the caller to ensure that the contents of event, params, and num\_params arguments are appropriate for the specified routine, and if necessary, that the specified widget is realized or sensitive. If the named action routine cannot be found, XtCallActionProc generates a warning message and returns.

SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtCallActionProc(3)