



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtGetActionList.3'***

**\$ man XtGetActionList.3**

XtGetActionList(3)                    XT FUNCTIONS                    XtGetActionList(3)

**NAME**

XtGetActionList - obtain class action list

**SYNTAX**

```
#include <X11/Intrinsic.h>
```

```
void XtGetActionList(WidgetClass widget_class, XtActionList* actions_return, Cardinal*  
num_actions_return);
```

**ARGUMENTS**

widget\_class

Specifies the widget class whose actions are to be returned.

actions\_return

Returns the action list.

num\_actions\_return

Returns the number of action procedures declared by the class.

**DESCRIPTION**

XtGetActionList returns the action table defined by the specified widget class. This ta?

ble does not include actions defined by the superclasses. If widget\_class is not initialized, or is not coreWidgetClass or a subclass thereof, or if the class does not define any actions, \*actions\_return will be NULL and \*num\_actions\_return will be zero. If \*actions\_return is non-NULL the client is responsible for freeing the table using XtFree when it is no longer needed.

#### SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtGetActionList(3)