



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtGetSelectionRequest.3'***

***\$ man XtGetSelectionRequest.3***

XtGetSelectionRequest(3)                      XT FUNCTIONS                      XtGetSelectionRequest(3)

**NAME**

XtGetSelectionRequest - retrieve the event that triggered the XtConvertSelectionProc

**SYNTAX**

```
#include <X11/Intrinsic.h>
```

```
XSelectionRequestEvent* XtGetSelectionRequest(Widget w, Atom selection, XtRequestId re?  
quest_id);
```

**ARGUMENTS**

w        Specifies the widget.

selection Specifies the selection being processed.

request\_id

Specifies the requestor id in the case of incremental selections, or NULL in the case of atomic transfers.

**DESCRIPTION**

XtGetSelectionRequest may only be called from within an XtConvertSelectionProc procedure and returns a pointer to the SelectionRequest event that caused the conversion procedure

to be invoked. Request\_id specifies a unique id for the individual request in the case that multiple incremental transfers are outstanding. For atomic transfers, request\_id must be specified as NULL. If no SelectionRequest event is being processed for the specified widget, selection, and request\_id, XtGetSelectionRequest returns NULL.

#### SEE ALSO

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface

X Version 11

libXt 1.2.1

XtGetSelectionRequest(3)