Rocky Enterprise Linux 9.2 Manual Pages on command 'XtRegisterDrawable.3'

$ man XtRegisterDrawable.3

XtRegisterDrawable(3)　　　　　　XT FUNCTIONS　　　　　　XtRegisterDrawable(3)

NAME

XtRegisterDrawable - register a drawable with the Intrinsics event dispatcher

SYNTAX

#include <X11/Intrinsic.h>

void XtRegisterDrawable(Display* display, Drawable drawable, Widget widget);

void XtUnregisterDrawable(Display* display, Drawable drawable);

ARGUMENTS

display　　Specifies the drawable's display.

drawable　Specifies the drawable to register.

widget　　Specifies the widget to register the drawable for.

DESCRIPTION

XtRegisterDrawable associates the specified drawable with the specified widget so that fu?

ture calls to XtWindowToWidget with the drawable will return the widget. The default

event dispatcher will dispatch future core events that arrive with the drawable to the

widget as though the event contained the widget's window, but the event itself will not be changed in any way when being passed to even handler or action procedures.

If the drawable is already registered with another widget, or if the drawable is the win? dow of a widget in the client's widget tree, the results of calling XtRegisterDrawable are undefined.

XtUnregisterDrawable removes an association created with XtRegisterDrawable. If the draw? able is the window of a widget in the client's widget tree the results of calling XtUnregisterDrawable are undefined.

SEE ALSO

X Toolkit Intrinsics - C Language Interface

Xlib - C Language X Interface

X Version 11   libXt 1.2.1   XtRegisterDrawable(3)