



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'XtVaGetSubresources.3'***

**\$ man XtVaGetSubresources.3**

XtGetSubresources(3)                      XT FUNCTIONS                      XtGetSubresources(3)

**NAME**

XtGetSubresources, XtVaGetSubresources - obtain subresources

**SYNTAX**

```
#include <X11/Intrinsic.h>
```

```
void XtGetSubresources(Widget w, XtPointer base, const char *name, const char * class,  
                        XtResourceList resources, Cardinal num_resources, ArgList args, Cardinal num_args);
```

```
void XtVaGetSubresources(Widget w, XtPointer base, const char *name, const char *class,  
                          XtResourceList resources, Cardinal num_resources, ...);
```

**ARGUMENTS**

args     Specifies the argument list to override resources obtained from the resource database.

base     Specifies the base address of the subpart data structure where the resources should be written.

class    Specifies the class of the subpart.

name Specifies the name of the subpart.

num\_args Specifies the number of arguments in the argument list.

num\_resources

Specifies the number of resources in the resource list.

resources Specifies the resource list for the subpart.

w Specifies the widget that wants resources for a subpart or that identifies the resource database to search.

... Specifies the variable arguments to override resources obtained from the resource database.

## DESCRIPTION

The `XtGetSubresources` function constructs a name/class list from the application name/class, the name/classes of all its ancestors, and the widget itself. Then, it appends to this list the name/class pair passed in. The resources are fetched from the argument list, the resource database, or the default values in the resource list. Then, they are copied into the subpart record. If `args` is `NULL`, `num_args` must be zero. However, if `num_args` is zero, the argument list is not referenced.

## SEE ALSO

`XtGetApplicationResources`, `XtVaGetApplicationResources`

X Toolkit Intrinsic - C Language Interface

Xlib - C Language X Interface