



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'a2disconf.8'***

**\$ man a2disconf.8**

A2ENCONF(8)                      System Manager's Manual                      A2ENCONF(8)

**NAME**

a2enconf, a2disconf - enable or disable an apache2 configuration file

**SYNOPSIS**

a2enconf [-q|--quiet] [-m|--maintmode] [ configuration ]  
a2disconf [-q|--quiet] [-m|--maintmode] [-p|--purge] [ configuration ]

**DESCRIPTION**

This manual page documents briefly the a2enconf and a2disconf commands.

a2enconf is a script that enables the specified configuration file within the apache2 configuration. It does this by creating symlinks within /etc/apache2/conf-enabled. Likewise, a2disconf disables a specific configuration part by removing those symlinks. It is not an error to enable a configuration which is already enabled, or to disable one which is already disabled.

Note that many configuration file may have a dependency to specific modules. Unlike module dependencies, these are not resolved automatically. Configuration fragments stored in the conf-available directory are considered non-essential or being installed and managed by reverse dependencies (e.g. web scripts).

**OPTIONS**

- q, --quiet  
Don't show informative messages.
- m, --maintmode  
Enables the maintainer mode, that is the program invocation is effectuated automatically by a maintainer script. This switch should not be used by end users.

-p, --purge

When disabling a module, purge all traces of the module in the internal state data base.

## EXIT STATUS

a2enconf and a2disconf exit with status 0 if all configurations are processed successfully, 1 if errors occur, 2 if an invalid option was used.

## EXAMPLES

a2enconf security

a2disconf charset

Enables Apache security directives stored in the security configuration files, and disables the charset configuration.

## FILES

/etc/apache2/conf-available

Directory with files giving information on available configuration files.

/etc/apache2/conf-enabled

Directory with links to the files in conf-available for enabled configuration files.

## SEE ALSO

apache2ctl(8), a2enmod(8), a2dismod(8), a2ensite(8), a2dissite(8).

## AUTHOR

This manual page was written by Arno Toell <debian@toell.net> for the Debian GNU/Linux distribution, as it is a Debian-specific script with the package.

14 February 2012

A2ENCONF(8)