



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'a2enmod.8'***

**\$ man a2enmod.8**

A2ENMOD(8)                      System Manager's Manual                      A2ENMOD(8)

**NAME**

a2enmod, a2dismod - enable or disable an apache2 module

**SYNOPSIS**

a2enmod [-q|--quiet] [-m|--maintmode] [ module ]

a2dismod [-q|--quiet] [-f|--force] [-m|--maintmode] [-p|--purge] [ module ]

**DESCRIPTION**

This manual page documents briefly the a2enmod and a2dismod commands.

a2enmod is a script that enables the specified module within the apache2 configuration.

It does this by creating symlinks within /etc/apache2/mods-enabled. Likewise, a2dismod disables a module by removing those symlinks. It is not an error to enable a module which is already enabled, or to disable one which is already disabled.

Note that many modules have, in addition to a .load file, an associated .conf file. En?

abling the module puts the configuration directives in the .conf file as directives into the main server context of apache2.

**OPTIONS**

-q, --quiet

Don't show informative messages.

-f, --force

When disabling a module, also cascade disables all modules that depends on it.

-m, --maintmode

Enables the maintainer mode, that is the program invocation is effectuated automat?

ically by a maintainer script. This switch should not be used by end users.

-p, --purge

When disabling a module, purge all traces of the module in the internal state data base.

## EXIT STATUS

a2enmod and a2dismod exit with status 0 if all modules are processed successfully, 1 if errors occur, 2 if an invalid option was used.

## EXAMPLES

```
a2enmod imagemap
```

```
a2dismod mime_magic
```

Enables the mod\_imagemap module, and disables the mod\_mime\_magic module.

## FILES

```
/etc/apache2/mods-available
```

Directory with files giving information on available modules.

```
/etc/apache2/mods-enabled
```

Directory with links to the files in mods-available for enabled modules.

## SEE ALSO

apache2ctl(8), a2enconf(8), a2disconf(8), a2ensite(8), a2dissite(8).

## AUTHOR

This manual page was written by Daniel Stone <daniel@sfarc.net> for the Debian GNU/Linux distribution, as it is a Debian-specific script with the package.

12 October 2006

A2ENMOD(8)