



Linux Ubuntu 22.4.5 Manual Pages on command 'aptitude-create-state-bundle.1'

\$ man aptitude-create-state-bundle.1

APTITUDE-CREATE-ST(1) Command-line reference APTITUDE-CREATE-ST(1)

NAME

aptitude-create-state-bundle - bundle the current aptitude state

SYNOPSIS

aptitude-create-state-bundle [<options>...] <output-file>

DESCRIPTION

Note

This command is mostly for internal use and bug reporting in exceptional cases, it is not intended for end-users under normal circumstances.

aptitude-create-state-bundle produces a compressed archive storing the files that are required to replicate the current package archive state. The following files and directories are included in the bundle:

- ? \$HOME/.aptitude
- ? /var/lib/aptitude
- ? /var/lib/apt
- ? /var/cache/apt/*.bin
- ? /etc/apt
- ? /var/lib/dpkg/status

The output of this program can be used as an argument to aptitude-run-state-bundle(1).

OPTIONS

--force-bzip2

Override the autodetection of which compression algorithm to use. By default, `aptitude-create-state-bundle` uses `bzip2(1)` if it is available, and `gzip(1)` otherwise. Passing this option forces the use of `bzip2` even if it doesn't appear to be available.

`--force-gzip`

Override the autodetection of which compression algorithm to use. By default, `aptitude-create-state-bundle` uses `bzip2(1)` if it is available, and `gzip(1)` otherwise. Passing this option forces the use of `gzip` even if `bzip2` is available.

`--help`

Print a brief usage message, then exit.

`--print-inputs`

Instead of creating a bundle, display a list of the files and directories that the program would include if it generated a bundle.

FILE FORMAT

The bundle file is simply a `tar(1)` file compressed with `bzip2(1)` or `gzip(1)`, with each of the input directory trees rooted at `??`.

SEE ALSO

`aptitude-run-state-bundle(1)`, `aptitude(8)`, `apt(8)`

AUTHORS

Daniel Burrows <dburrows@debian.org>

Main author of the document.

Manuel A. Fernandez Montecelo <maf@debian.org>

Main maintainer after Daniel Burrows, documentation about new features, corrections and formatting.

COPYRIGHT

Copyright 2007 Daniel Burrows.

This manual page is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This manual page is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA.

aptitude-create-state-bundle 0

02/27/2020

APTITUDE-CREATE-ST(1)