



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'atof.3'

\$ man atof.3

ATOF(3) Linux Programmer's Manual ATOF(3)

NAME

atof - convert a string to a double

SYNOPSIS

```
#include <stdlib.h>

double atof(const char *nptr);
```

DESCRIPTION

The atof() function converts the initial portion of the string pointed to by nptr to double. The behavior is the same as strtod(nptr, NULL); except that atof() does not detect errors.

RETURN VALUE

The converted value.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?atof() ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C89, C99, SVr4, 4.3BSD.

SEE ALSO

atoi(3), atol(3), strfromd(3), strtod(3), strtol(3), strtoul(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2016-12-12

ATOF(3)