



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'btattach.1'

\$ man btattach.1

BTATTACH(1) Linux System Administration BTATTACH(1)

NAME

btattach - Attach serial devices to BlueZ stack

SYNOPSIS

btattach [-B device] [-A device] [-P protocol] [-R]

DESCRIPTION

btattach(1) is used to attach a serial UART to the Bluetooth stack as a transport interface.

OPTIONS

-B device, --brder device

Attach a BR/EDR controller

-A device, --amp device

Attach an AMP controller

-P protocol, --protocol protocol

Specify the protocol type for talking to the device.

Supported values are:

????????????

?protocol ?

????????????

?h4 ?

????????????

?bcsp ?

????????????

?3wire ?

????????????

?h4ds ?

????????????

?ll ?

????????????

?ath3k ?

????????????

?intel ?

????????????

?bcm ?

????????????

?qca ?

????????????

-S baudrate, --speed baudrate

Specify wich baudrate to use

-N, --noflowctl

Disable flow control

-v, --version

Show version

-h, --help

Show help options

RESOURCES

<http://www.bluez.org>

REPORTING BUGS

linux-bluetooth@vger.kernel.org

COPYRIGHT

Free use of this software is granted under the terms of the GNU Lesser General Public License (LGPL).

BlueZ

November 2015

BTATTACH(1)