



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'buildah-logout.1'***

***\$ man buildah-logout.1***

buildah-logout(1)                    General Commands Manual                    buildah-logout(1)

NAME

buildah-logout - Logout of a container registry

SYNOPSIS

buildah logout [options] registry

DESCRIPTION

buildah logout logs out of a specified registry server by deleting the cached credentials stored in the auth.json file. The path of the authentication file can be overridden by the user by setting the authfile flag. The default path used is `$(XDG_RUNTIME_DIR)/containers/auth.json`. If `XDG_RUNTIME_DIR` is not set, the default is `/run/containers/$UID/auth.json`. All the cached credentials can be removed by setting the all flag.

buildah [GLOBAL OPTIONS]

buildah logout [GLOBAL OPTIONS]

buildah logout [OPTIONS] REGISTRY [GLOBAL OPTIONS]

OPTIONS

--all, -a

Remove the cached credentials for all registries in the auth file

--authfile

Path of the authentication file. Default is `$(XDG_RUNTIME_DIR)/containers/auth.json`. If `XDG_RUNTIME_DIR` is not set, the default is `/run/containers/$UID/auth.json`.

Note: You can also override the default path of the authentication file by setting the `REGISTRY_AUTH_FILE` environment variable. `export REGISTRY_AUTH_FILE=path`

--help, -h

Print usage statement

## EXAMPLES

```
$ buildah logout docker.io
```

Removed login credentials for docker.io

```
$ buildah logout --authfile authdir/myauths.json docker.io
```

Removed login credentials for docker.io

```
$ buildah logout --all
```

Remove login credentials for all registries

## SEE ALSO

[buildah\(1\)](#), [buildah-login\(1\)](#)

[buildah](#)

Apr 2019

[buildah-logout\(1\)](#)