



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'buildah-manifest-push.1'

\$ man buildah-manifest-push.1

buildah-manifest-push(1) General Commands Manual buildah-manifest-push(1)

NAME

buildah-manifest-push - Push a manifest list or image index to a registry.

SYNOPSIS

buildah manifest push [options...] listNameOrIndexName transport:details

DESCRIPTION

Pushes a manifest list or image index to a registry.

RETURN VALUE

The list image's ID and the digest of the image's manifest.

OPTIONS

--all

Push the images mentioned in the manifest list or image index, in addition to the list or index itself.

--authfile path

Path of the authentication file. Default is `${XDG_RUNTIME_DIR}/containers/auth.json`, which is set using buildah login. If the authorization state is not found there, `$HOME/.docker/config.json` is checked, which is set using docker login.

--cert-dir path

Use certificates at path (*.crt, *.cert, *.key) to connect to the registry. The default certificates directory is `/etc/containers/certs.d`.

--creds creds

The `[username[:password]]` to use to authenticate with the registry if required. If one or both values are not supplied, a command line prompt will appear and the value can be entered.

tered. The password is entered without echo.

--digestfile Digestfile

After copying the image, write the digest of the resulting image to the file.

--format, -f

Manifest list type (oci or v2s2) to use when pushing the list (default is oci).

--quiet, -q

Don't output progress information when pushing lists.

--remove-signatures

Don't copy signatures when pushing images.

--rm

Delete the manifest list or image index from local storage if pushing succeeds.

--sign-by fingerprint

Sign the pushed images using the GPG key that matches the specified fingerprint.

--tls-verify bool-value

Require HTTPS and verification of certificates when talking to container registries (defaults to true). TLS verification cannot be used when talking to an insecure registry.

EXAMPLE

```
buildah manifest push mylist:v1.11 docker://registry.example.org/mylist:v1.11
```

SEE ALSO

buildah(1), buildah-login(1), buildah-manifest(1), buildah-manifest-create(1), buildah-manifest-add(1), buildah-manifest-remove(1), buildah-manifest-annotate(1), buildah-manifest-inspect(1), buildah-rmi(1), docker-login(1)

buildah

September 2019

buildah-manifest-push(1)