



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'casinl.3'

\$ man casinl.3

CASIN(3) Linux Programmer's Manual CASIN(3)

NAME

casin, casinl, casinl - complex arc sine

SYNOPSIS

```
#include <complex.h>

double complex casin(double complex z);

float complex casinf(float complex z);

long double complex casinl(long double complex z);

Link with -lm.
```

DESCRIPTION

These functions calculate the complex arc sine of z. If $y = \text{casin}(z)$, then $z = \text{csin}(y)$. The real part of y is chosen in the interval $[-\pi/2, \pi/2]$. One has:

$$\text{casin}(z) = -i \log(iz + \text{csqrt}(1 - z * z))$$

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?casin(), casinf(), casinl() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

SEE ALSO

`clog(3)`, `csin(3)`, `complex(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2015-04-19

CASIN(3)