



Linux Ubuntu 22.4.5 Manual Pages on command 'cifsio`stat.1`'

`$ man cifsiostat.1`

CIFSIOSTAT(1) Linux User's Manual CIFSIOSTAT(1)

NAME

`cifsiostat` - Report CIFS statistics.

SYNOPSIS

```
cifsiostat [ -h ] [ -k | -m ] [ -t ] [ -V ] [ --dec={ 0 | 1 | 2 } ] [ --human ] [
interval [ count ] ]
```

DESCRIPTION

The `cifsiostat` command displays statistics about read and write operations on CIFS filesystems.

The interval parameter specifies the amount of time in seconds between each report.

The first report contains statistics for the time since system startup (boot). Each

subsequent report contains statistics collected during the interval since the pre-

vious report. A report consists of a CIFS header row followed by a line of statis-

tics for each CIFS filesystem that is mounted. The count parameter can be speci-

fied in conjunction with the interval parameter. If the count parameter is speci-

fied, the value of count determines the number of reports generated at interval

seconds apart. If the interval parameter is specified without the count parameter,

the `cifsiostat` command generates reports continuously.

REPORT

The CIFS report provides statistics for each mounted CIFS filesystem. The report shows the following fields:

Filesystem:

This column shows the mount point of the CIFS filesystem.

rB/s (rkB/s, rMB/s)

Indicate the average number of bytes (kilobytes, megabytes) read per second.

wB/s (wkB/s, wMB/s)

Indicate the average number of bytes (kilobytes, megabytes) written per second.

rop/s

Indicate the number of 'read' operations that were issued to the filesystem per second.

wop/s

Indicate the number of 'write' operations that were issued to the filesystem per second.

fo/s

Indicate the number of open files per second.

fc/s

Indicate the number of closed files per second.

fd/s

Indicate the number of deleted files per second.

OPTIONS

--dec={ 0 | 1 | 2 }

Specify the number of decimal places to use (0 to 2, default value is 2).

-h Make the CIFS report easier to read by a human. --human is enabled implicitly with this option.

--human

Print sizes in human readable format (e.g. 1.0k, 1.2M, etc.) The units displayed with this option supersede any other default units (e.g. kilobytes, sectors...) associated with the metrics.

-k Display statistics in kilobytes per second.

-m Display statistics in megabytes per second.

-t Print the time for each report displayed. The timestamp format may depend on the value of the S_TIME_FORMAT environment variable (see below).

-V Print version number then exit.

ENVIRONMENT

The cifsostat command takes into account the following environment variables:

S_COLORS

When this variable is set, display statistics in color on the terminal.

Possible values for this variable are never, always or auto (the latter is the default).

Note: On Debian systems the colors are displayed by default when output is connected to the terminal, even if this variable is not set (i.e. unset variable is treated as if it were set to auto).

Please note that the color (being red, yellow, or some other color) used to display a value is not indicative of any kind of issue simply because of the color. It only indicates different ranges of values.

S_COLORS_SGR

Specify the colors and other attributes used to display statistics on the terminal. Its value is a colon-separated list of capabilities that defaults to l=32;22:N=34;1:Z=34;22. Supported capabilities are:

l= SGR substring for filesystem names.

N= SGR substring for non-zero statistics values.

Z= SGR substring for zero values.

S_TIME_FORMAT

If this variable exists and its value is ISO then the current locale will be ignored when printing the date in the report header. The cifsostat command will use the ISO 8601 format (YYYY-MM-DD) instead. The timestamp displayed with option -t will also be compliant with ISO 8601 format.

BUG

/proc filesystem must be mounted for cifsostat to work.

FILE

/proc/fs/cifs/Stats contains CIFS statistics.

AUTHORS

Written by Ivana Varekova (varekova <at> redhat.com)

Maintained by Sebastien Godard (sysstat <at> orange.fr)

SEE ALSO

sar(1), pidstat(1), mpstat(1), vmstat(8), iostat(1), tapestat(1), nfsiostat(1)

<https://github.com/sysstat/sysstat>

