



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'cimagf.3'

\$ man cimagf.3

CIMAG(3) Linux Programmer's Manual CIMAG(3)

NAME

cimag, cimagf, cimagl - get imaginary part of a complex number

SYNOPSIS

```
#include <complex.h>

double cimag(double complex z);

float cimagf(float complex z);

long double cimagl(long double complex z);

Link with -lm.
```

DESCRIPTION

These functions return the imaginary part of the complex number z.
One has:

$$z = \text{creal}(z) + I * \text{cimag}(z)$$

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).
??
?Interface ? Attribute ? Value ?
??
?cimag(), cimagf(), cimagl() ? Thread safety ? MT-Safe ?
??

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

NOTES

gcc also supports `__imag__`. That is a GNU extension.

SEE ALSO

`cabs(3)`, `creal(3)`, `complex(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2015-04-19

CIMAG(3)