



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

## ***Rocky Enterprise Linux 9.2 Manual Pages on command 'containers-registries.conf.d.5'***

***\$ man containers-registries.conf.d.5***

CONTAINERS-REGISTRIES.CONF.D(5)    File Formats Manual    CONTAINERS-REGISTRIES.CONF.D(5)

Valentin Rothberg Mar 2020

### NAME

containers-registries.conf.d - directory for drop-in registries.conf files

### DESCRIPTION

CONTAINERS-REGISTRIES.CONF.D is a system-wide directory for drop-in configuration files in the containers-registries.conf(5) format.

By default, the directory is located at `/etc/containers/registries.conf.d`.

### CONFIGURATION PRECEDENCE

Once the main configuration at `/etc/containers/registries.conf` is loaded, the files in `/etc/containers/registries.conf.d` are loaded in alpha-numerical order. Then the conf files in `$HOME/.config/containers/registries.conf.d` are loaded in alpha-numerical order, if they exist. If the `$HOME/.config/containers/registries.conf` is loaded, only the conf files under `$HOME/.config/containers/registries.conf.d` are loaded in alpha-numerical order. Specified fields in a conf file will overwrite any previous setting. Note that only files with the `.conf` suffix are loaded, other files and sub-directories are ignored.

For instance, setting the `unqualified-search-registries` in `/etc/containers/reg?`

registries.conf.d/myregistries.conf will overwrite previous settings in /etc/containers/registries.conf. The [[registry]] tables merged by overwriting existing items if the prefixes are identical while new ones are added.

All drop-in configuration files must be specified in the version 2 of the containers-registries.conf(5) format.

## SEE ALSO

containers-registries.conf(5)

## HISTORY

Mar 2020, Originally compiled by Valentin Rothberg [rothberg@redhat.com](mailto:rothberg@redhat.com)

CONTAINERS-REGISTRIES.CONF.D(5)