



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'cupsreject.8'

\$ man cupsreject.8

cupsaccept(8) OpenPrinting cupsaccept(8)

NAME

cupsaccept/cupsreject - accept/reject jobs sent to a destination

SYNOPSIS

cupsaccept [-E] [-U username] [-h hostname[:port]] destination(s)

cupsreject [-E] [-U username] [-h hostname[:port]] [-r reason] destination(s)

DESCRIPTION

The cupsaccept command instructs the printing system to accept print jobs to the specified destinations.

The cupsreject command instructs the printing system to reject print jobs to the specified destinations. The -r option sets the reason for rejecting print jobs. If not specified, the reason defaults to "Reason Unknown".

OPTIONS

The following options are supported by both cupsaccept and cupsreject:

-E Forces encryption when connecting to the server.

-U username

Sets the username that is sent when connecting to the server.

-h hostname[:port]

Chooses an alternate server.

-r "reason"

Sets the reason string that is shown for a printer that is rejecting jobs.

CONFORMING TO

The cupsaccept and cupsreject commands correspond to the System V printing system commands

"accept" and "reject", respectively. Unlike the System V printing system, CUPS allows printer names to contain any printable character except SPACE, TAB, "/", or "#". Also, printer and class names are not case-sensitive.

Finally, the CUPS versions may ask the user for an access password depending on the printing system configuration.

SEE ALSO

cancel(1), cupsenable(8), lp(1), lpadmin(8), lpstat(1),

CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright ? 2021-2022 by OpenPrinting.

2021-02-28

CUPS

cupsaccept(8)