



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'deluser.conf.5'

\$ man deluser.conf.5

deluser.conf(5) File Formats Manual deluser.conf(5)

NAME

/etc/deluser.conf - configuration file for deluser(8) and delgroup(8).

DESCRIPTION

The file */etc/deluser.conf* contains defaults for the programs deluser(8) and delgroup(8). Each option takes the form option = value. Double or single quotes are allowed around the value. Comment lines must have a hash sign (#) at the beginning of the line.

deluser(8) and delgroup(8) also read */etc/adduser.conf*, see adduser.conf(5); settings in *deluser.conf* may overwrite settings made in *adduser.conf*.

The valid configuration options are:

REMOVE_HOME

Removes the home directory and mail spool of the user to be removed. Value may be 0 (don't delete) or 1 (do delete).

REMOVE_ALL_FILES

Removes all files on the system owned by the user to be removed. If this option is activated REMOVE_HOME has no effect. Values may be 0 or 1.

BACKUP If REMOVE_HOME or REMOVE_ALL_FILES is activated all files are backed up before they are removed. The backup file that is created defaults to username.tar(.gz|.bz2) in the directory specified by the BACKUP_TO option. The compression method is chosen to the best that is available. Values may be 0 or 1.

BACKUP_TO

If BACKUP is activated, BACKUP_TO specifies the directory the backup is written to. Default is the current directory.

NO_DEL_PATHS

A list of regular expressions, space separated. All files to be deleted in course of deleting home directories or deleting files owned by the user to be deleted are checked against each of these regular expressions. If a match is detected, the file is not deleted. Defaults to a list of system directories, leaving only /home.

In other words: By default only files below /home belonging to that specific user are going to be deleted.

ONLY_IF_EMPTY

Only delete a group if there are no users belonging to this group. Defaults to 0.

EXCLUDE_FSTYPES

A regular expression which describes all file systems which should be excluded when looking for files of a user to be deleted. Defaults to "(proc|sysfs|usbfs|dev|vpts|tmpfs|afs)".

FILES

/etc/deluser.conf

SEE ALSO

adduser.conf(5), delgroup(8), deluser(8)