



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'dmmp_path_array_get.3'

\$ man dmmp_path_array_get.3

dmmp_path_array_get(3) Device Mapper Multipath API - libdmmp Manual dmmp_path_array_get(3)

NAME

dmmp_path_array_get - Retrieve path pointer array.

SYNOPSIS

```
void dmmp_path_array_get (struct dmmp_path_group *dmmp_pg, struct dmmp_path ***dmmp_ps,  
uint32_t *dmmp_p_count);
```

ARGUMENTS

dmmp_pg Pointer of 'struct dmmp_path_group'. If this pointer is NULL, your program will be terminated by assert.

dmmp_ps Output pointer of 'struct dmmp_path' pointer array. If this pointer is NULL, your program will be terminated by assert.

dmmp_p_count

Output pointer of uint32_t. Hold the size of 'dmmp_ps' pointer array. If this pointer is NULL, your program will be terminated by assert.

DESCRIPTION

The memory of output pointer array is hold by 'struct dmmp_mpath', no need to free this memory, the resources will got freed when dmmp_mpath_array_free.

RETURN

void

March 2018

dmmp_path_array_get

dmmp_path_array_get(3)