

MyWebUniversity

Manual Pages  
ubuntu  
Linux for the environment



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'docker-image-unmount.1'***

**\$ man docker-image-unmount.1**

```
podman-image-unmount(1())          podman-image-unmount(1())
```

#### **NAME**

podman-image-unmount - Unmount an image's root filesystem

#### **SYNOPSIS**

```
podman image unmount [options] image [...]
```

```
podman image umount [options] image [...]
```

#### **DESCRIPTION**

Unmounts the specified images' root file system, if no other processes are using it.

Image storage increments a mount counter each time an image is mounted. When a image is unmounted, the mount counter is decremented, and the image's root filesystem is physically unmounted only when the mount counter reaches zero indicating no other processes are using the mount. An unmount can be forced with the `--force` flag.

#### **OPTIONS**

`--all, -a`

All of the currently mounted images will be unmounted.

`--force, -f`

Force the unmounting of specified images' root file system, even if other processes have mounted it.

Note: This could cause other processes that are using the file system to fail, as the mount point could be removed without their knowledge.

#### **EXAMPLE**

```
podman image unmount imageID
```

```
podman image unmount imageID1 imageID2 imageID3
```

podman image unmount --all

SEE ALSO

podman(1), podman-image-mount(1), podman-container-mount(1)

podman-image-unmount(1)()