



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'dpkg-preconfigure.8'

\$ man dpkg-preconfigure.8

DPKG-PRECONFIGURE(8) Debconf DPKG-PRECONFIGURE(8)

NAME

dpkg-preconfigure - let packages ask questions prior to their installation

SYNOPSIS

dpkg-preconfigure [options] package.deb

dpkg-preconfigure --apt

DESCRIPTION

dpkg-preconfigure lets packages ask questions before they are installed. It operates on a set of debian packages, and all packages that use debconf will have their config script run so they can examine the system and ask questions.

OPTIONS

-ftype, --frontend=type

Select the frontend to use.

-pvalue, --priority=value

Set the lowest priority of questions you are interested in. Any questions with a priority below the selected priority will be ignored and their default answers will be used.

`--terse`

Enables terse output mode. This affects only some frontends.

`--apt`

Run in apt mode. It will expect to read a set of package filenames from stdin, rather than getting them as parameters. Typically this is used to make apt run dpkg-preconfigure on all packages before they are installed. To do this, add something like this to `/etc/apt/apt.conf`:

```
// Pre-configure all packages before
// they are installed.
DPkg::Pre-Install-Pkgs {
    "dpkg-preconfigure --apt --priority=low";
};
```

`-h, --help`

Display usage help.

SEE ALSO

`debconf(7)`

AUTHOR

Joey Hess <joeyh@debian.org>

2022-02-20

DPKG-PRECONFIGURE(8)