



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'drand48\_r.3'***

***\$ man drand48\_r.3***

DRAND48\_R(3)                      Linux Programmer's Manual                      DRAND48\_R(3)

NAME

drand48\_r, erand48\_r, lrand48\_r, nrand48\_r, mrand48\_r, jrand48\_r, srand48\_r, seed48\_r,  
lcong48\_r - generate uniformly distributed pseudo-random numbers reentrantly

SYNOPSIS

```
#include <stdlib.h>

int drand48_r(struct drand48_data *buffer, double *result);

int erand48_r(unsigned short xsubi[3],
             struct drand48_data *buffer, double *result);

int lrand48_r(struct drand48_data *buffer, long *result);

int nrand48_r(unsigned short xsubi[3],
             struct drand48_data *buffer, long *result);

int mrand48_r(struct drand48_data *buffer, long *result);

int jrand48_r(unsigned short xsubi[3],
             struct drand48_data *buffer, long *result);

int srand48_r(long int seedval, struct drand48_data *buffer);

int seed48_r(unsigned short seed16v[3],
            struct drand48_data *buffer);

int lcong48_r(unsigned short param[7],
            struct drand48_data *buffer);
```

Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)):

All functions shown above:

```
/* Glibc since 2.19: */ _DEFAULT_SOURCE
```

|| /\* Glibc versions <= 2.19: \*/ \_SVID\_SOURCE || \_BSD\_SOURCE

DESCRIPTION

These functions are the reentrant analogs of the functions described in drand48(3). In?
stead of modifying the global random generator state, they use the supplied data buffer.

Before the first use, this struct must be initialized, for example, by filling it with ze?
ros, or by calling one of the functions srand48\_r(), seed48\_r(), or lcong48\_r().

RETURN VALUE

The return value is 0.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?drand48\_r(), erand48\_r(), ? Thread safety ? MT-Safe race:buffer ?

?lrand48\_r(), nrand48\_r(), ? ? ?

?mrand48\_r(), jrand48\_r(), ? ? ?

?srand48\_r(), seed48\_r(), ? ? ?

?lcong48\_r() ? ? ?

??

CONFORMING TO

These functions are GNU extensions and are not portable.

SEE ALSO

drand48(3), rand(3), random(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the
project, information about reporting bugs, and the latest version of this page, can be
found at https://www.kernel.org/doc/man-pages/.