



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'fc-list.1'

\$ man fc-list.1

FC-LIST(1)

FC-LIST(1)

NAME

fc-list - list available fonts

SYNOPSIS

```
fc-list [ -vVh ] [ --verbose ] [ [ -f format ] [ --format format ] ] [ [ -q ] [
--quiet ] ] [ --version ] [ --help ]
[ pattern [ element... ] ]
```

DESCRIPTION

fc-list lists fonts and styles available on the system for applications using fontconfig.

If any elements are specified, only those are printed. Otherwise family and style are printed, unless verbose output is requested.

OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

- v Print verbose output of the whole font pattern for each match, or elements if any is provided.
- f Format output according to the format specifier format.
- q Suppress all normal output. returns 1 as the error code if no fonts matched.
- V Show version of the program and exit.
- h Show summary of options.

pattern

If this argument is set, only fonts matching pattern are displayed.

element

If set, the element property is displayed for matching fonts.

EXAMPLES

`fc-list`

Lists all font faces.

`fc-list :lang=hi`

Lists font faces that cover Hindi.

`fc-list : family style file spacing`

Lists the filename and spacing value for each font face. ``:" is an empty pattern that matches all fonts.

SEE ALSO

`fc-match(1)` `FcFontList(3)` `FcPatternFormat(3)` `fc-cat(1)` `fc-cache(1)` `fc-pattern(1)` `fc-query(1)` `fc-scan(1)`

The fontconfig user's guide, in HTML format: `/usr/share/doc/fontconfig/fontconfig-user.html`.

AUTHOR

This manual page was written by Keith Packard <keithp@keithp.com> and Josselin Mouette <joss@debian.org>.

Aug 13, 2008

FC-LIST(1)