



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'fcloseall.3'

\$ man fcloseall.3

FCLOSEALL(3) Linux Programmer's Manual FCLOSEALL(3)

NAME

fcloseall - close all open streams

SYNOPSIS

```
#define _GNU_SOURCE        /* See feature_test_macros(7) */
#include <stdio.h>
int fcloseall(void);
```

DESCRIPTION

The fcloseall() function closes all of the calling process's open streams. Buffered output for each stream is written before it is closed (as for fflush(3)); buffered input is discarded.

The standard streams, stdin, stdout, and stderr are also closed.

RETURN VALUE

This function returns 0 if all files were successfully closed; on error, EOF is returned.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

????????????????????????????????????????????????????????????????

?Interface ? Attribute ? Value ?

????????????????????????????????????????????????????????????????

?fcloseall() ? Thread safety ? MT-Unsafe race:streams ?

????????????????????????????????????????????????????????????????

The fcloseall() function does not lock the streams, so it is not thread-safe.

CONFORMING TO

This function is a GNU extension.

SEE ALSO

close(2), fclose(3), fflush(3), fopen(3), setbuf(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2017-09-15

FCLOSEALL(3)