

Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'fdiml.3'

\$ man fdiml.3

FDIM(3) Linux Programmer's Manual FDIM(3) NAME fdim, fdimf, fdiml - positive difference SYNOPSIS #include <math.h> double fdim(double x, double y); float fdimf(float x, float y); long double fdiml(long double x, long double y); Link with -lm.

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

fdimf(), fdiml():

_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L

DESCRIPTION

These functions return the positive difference, max(x-y,0), between their arguments.

RETURN VALUE

On success, these functions return the positive difference.

If x or y is a NaN, a NaN is returned.

If the result overflows, a range error occurs, and the functions return HUGE_VAL,

 $\mathsf{HUGE_VALF},$ or $\mathsf{HUGE_VALL},$ respectively.

ERRORS

See math_error(7) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Range error: result overflow

errno is set to ERANGE. An overflow floating-point exception (FE_OVERFLOW) is

raised.

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

?Interface ? Attribute ? Value ?

?fdim(), fdimf(), fdiml() ? Thread safety ? MT-Safe ?

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

BUGS

Before glibc version 2.24 on certain architectures (e.g., x86, but not x86_64) these func? tions did not set errno.

SEE ALSO

fmax(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

2020-06-09 FDIM(3)