

Full credit is given to the above companies including the **Operating System (OS) that this PDF file was generated!**

Rocky Enterprise Linux 9.2 Manual Pages on command 'getpt.3'

\$ man getpt.3

GETPT(3)

Linux Programmer's Manual GETPT(3)

NAME

getpt - open a new pseudoterminal master

SYNOPSIS

#define _GNU_SOURCE /* See feature_test_macros(7) */

#include <stdlib.h>

int getpt(void);

DESCRIPTION

getpt() opens a new pseudoterminal device and returns a file descriptor that refers to

that device. It is equivalent to opening the pseudoterminal multiplexor device

open("/dev/ptmx", O_RDWR);

on Linux systems, though the pseudoterminal multiplexor device is located elsewhere on

some systems that use the GNU C library.

RETURN VALUE

getpt() returns an open file descriptor upon successful completion. Otherwise, it returns

-1 and sets errno to indicate the error.

ERRORS

getpt() can fail with various errors described in open(2).

VERSIONS

getpt() is provided in glibc since version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

?Interface ? Attribute ? Value ?

?getpt() ? Thread safety ? MT-Safe ?

CONFORMING TO

getpt() is glibc-specific; use posix_openpt(3) instead.

SEE ALSO

grantpt(3), posix_openpt(3), ptsname(3), unlockpt(3), ptmx(4), pty(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

GNU 2020-08-13 GETPT(3)