



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'git-mailsplit.1'

\$ man git-mailsplit.1

GIT-MAILSPLIT(1) Git Manual GIT-MAILSPLIT(1)

NAME

git-mailsplit - Simple UNIX mbox splitter program

SYNOPSIS

git mailsplit [-b] [-f<nn>] [-d<prec>] [--keep-cr] [--mboxrd]
 -o<directory> [--] [(<mbox>|<Maildir>)...]

DESCRIPTION

Splits a mbox file or a Maildir into a list of files: "0001" "0002" .. in the specified directory so you can process them further from there.

Important

Maildir splitting relies upon filenames being sorted to output patches in the correct order.

OPTIONS

<mbox>

Mbox file to split. If not given, the mbox is read from the standard input.

<Maildir>

Root of the Maildir to split. This directory should contain the cur, tmp and new

subdirectories.

`-o<directory>`

Directory in which to place the individual messages.

`-b`

If any file doesn't begin with a From line, assume it is a single mail message instead of signaling error.

`-d<prec>`

Instead of the default 4 digits with leading zeros, different precision can be specified for the generated filenames.

`-f<nn>`

Skip the first <nn> numbers, for example if `-f3` is specified, start the numbering with 0004.

`--keep-cr`

Do not remove `\r` from lines ending with `\r\n`.

`--mboxrd`

Input is of the "mboxrd" format and `"^>+From "` line escaping is reversed.

GIT

Part of the `git(1)` suite

Git 2.34.1

07/07/2023

GIT-MAILSPLIT(1)