



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'git-pack-redundant.1'***

***\$ man git-pack-redundant.1***

GIT-PACK-REDUNDANT(1)                      Git Manual                      GIT-PACK-REDUNDANT(1)

**NAME**

git-pack-redundant - Find redundant pack files

**SYNOPSIS**

git pack-redundant [ --verbose ] [ --alt-odb ] < --all | .pack filename ... >

**DESCRIPTION**

This program computes which packs in your repository are redundant. The output is suitable for piping to xargs rm if you are in the root of the repository.

git pack-redundant accepts a list of objects on standard input. Any objects given will be ignored when checking which packs are required. This makes the following command useful when wanting to remove packs which contain unreachable objects.

git fsck --full --unreachable | cut -d ' ' -f3 | \ git pack-redundant --all | xargs rm

**OPTIONS**

--all

Processes all packs. Any filenames on the command line are ignored.

--alt-odb

Don't require objects present in packs from alternate object directories to be present in local packs.

--verbose

Outputs some statistics to stderr. Has a small performance penalty.

**SEE ALSO**

git-pack-objects(1) git-repack(1) git-prune-packed(1)

Part of the git(1) suite

Git 2.34.1

07/07/2023

GIT-PACK-REDUNDANT(1)