



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'git-prune-packed.1'***

***\$ man git-prune-packed.1***

GIT-PRUNE-PACKED(1)                      Git Manual                      GIT-PRUNE-PACKED(1)

**NAME**

git-prune-packed - Remove extra objects that are already in pack files

**SYNOPSIS**

git prune-packed [-n|--dry-run] [-q|--quiet]

**DESCRIPTION**

This program searches the \$GIT\_OBJECT\_DIRECTORY for all objects that currently exist in a pack file as well as the independent object directories.

All such extra objects are removed.

A pack is a collection of objects, individually compressed, with delta compression applied, stored in a single file, with an associated index file.

Packs are used to reduce the load on mirror systems, backup engines, disk storage, etc.

**OPTIONS**

-n, --dry-run

Don't actually remove any objects, only show those that would have been removed.

-q, --quiet

Squelch the progress indicator.

#### SEE ALSO

[git-pack-objects\(1\)](#) [git-repack\(1\)](#)

#### GIT

Part of the [git\(1\)](#) suite

Git 2.34.1

07/07/2023

[GIT-PRUNE-PACKED\(1\)](#)