



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'git-receive-pack.1'

\$ man git-receive-pack.1

GIT-RECEIVE-PACK(1) Git Manual GIT-RECEIVE-PACK(1)

NAME

git-receive-pack - Receive what is pushed into the repository

SYNOPSIS

git-receive-pack <directory>

DESCRIPTION

Invoked by git send-pack and updates the repository with the information fed from the remote end.

This command is usually not invoked directly by the end user. The UI for the protocol is on the git send-pack side, and the program pair is meant to be used to push updates to remote repository. For pull operations, see git-fetch-pack(1).

The command allows for creation and fast-forwarding of sha1 refs (heads/tags) on the remote end (strictly speaking, it is the local end git-receive-pack runs, but to the user who is sitting at the send-pack end, it is updating the remote. Confused?)

There are other real-world examples of using update and post-update hooks found in the Documentation/howto directory.

git-receive-pack honours the receive.denyNonFastForwards config option, which tells it if updates to a ref should be denied if they are not fast-forwards.

A number of other receive.* config options are available to tweak its behavior, see git-config(1).

OPTIONS

<directory>

The repository to sync into.

--http-backend-info-refs

Used by git-http-backend(1) to serve up \$GIT_URL/info/refs?service=git-receive-pack requests. See --http-backend-info-refs in git-upload-pack(1).

PRE-RECEIVE HOOK

Before any ref is updated, if \$GIT_DIR/hooks/pre-receive file exists and is executable, it will be invoked once with no parameters. The standard input of the hook will be one line per ref to be updated:

```
sha1-old SP sha1-new SP refname LF
```

The refname value is relative to \$GIT_DIR; e.g. for the master head this is "refs/heads/master". The two sha1 values before each refname are the object names for the refname before and after the update. Refs to be created will have sha1-old equal to 0{40}, while refs to be deleted will have sha1-new equal to 0{40}, otherwise sha1-old and sha1-new should be valid objects in the repository.

When accepting a signed push (see git-push(1)), the signed push certificate is stored in a blob and an environment variable GIT_PUSH_CERT can be consulted for its object name. See the description of post-receive hook for an example. In addition, the certificate is verified using GPG and the result is exported with the following environment variables:

GIT_PUSH_CERT_SIGNER

The name and the e-mail address of the owner of the key that signed the push certificate.

GIT_PUSH_CERT_KEY

The GPG key ID of the key that signed the push certificate.

GIT_PUSH_CERT_STATUS

The status of GPG verification of the push certificate, using the same mnemonic as used in %G? format of git log family of commands (see git-log(1)).

GIT_PUSH_CERT_NONCE

The nonce string the process asked the signer to include in the push certificate. If this does not match the value recorded on the "nonce" header in the push certificate, it may indicate that the certificate is a valid one that is being replayed from a separate "git push" session.

GIT_PUSH_CERT_NONCE_STATUS

UNSOLICITED

"git push --signed" sent a nonce when we did not ask it to send one.

MISSING

"git push --signed" did not send any nonce header.

BAD

"git push --signed" sent a bogus nonce.

OK

"git push --signed" sent the nonce we asked it to send.

SLOP

"git push --signed" sent a nonce different from what we asked it to send now, but in a previous session. See `GIT_PUSH_CERT_NONCE_SLOP` environment variable.

`GIT_PUSH_CERT_NONCE_SLOP`

"git push --signed" sent a nonce different from what we asked it to send now, but in a different session whose starting time is different by this many seconds from the current session. Only meaningful when `GIT_PUSH_CERT_NONCE_STATUS` says SLOP. Also read about `receive.certNonceSlop` variable in `git-config(1)`.

This hook is called before any rename is updated and before any fast-forward checks are performed.

If the pre-receive hook exits with a non-zero exit status no updates will be performed, and the update, post-receive and post-update hooks will not be invoked either. This can be useful to quickly bail out if the update is not to be supported.

See the notes on the quarantine environment below.

UPDATE HOOK

Before each ref is updated, if `$GIT_DIR/hooks/update` file exists and is executable, it is invoked once per ref, with three parameters:

```
$GIT_DIR/hooks/update refname sha1-old sha1-new
```

The `refname` parameter is relative to `$GIT_DIR`; e.g. for the master head this is `"refs/heads/master"`. The two `sha1` arguments are the object names for the `refname` before and after the update. Note that the hook is called before the `refname` is updated, so either `sha1-old` is `0{40}` (meaning there is no such ref yet), or it should match what is recorded in `refname`.

The hook should exit with non-zero status if it wants to disallow updating the named ref.

Otherwise it should exit with zero.

Successful execution (a zero exit status) of this hook does not ensure the ref will actually be updated, it is only a prerequisite. As such it is not a good idea to send

notices (e.g. email) from this hook. Consider using the post-receive hook instead.

POST-RECEIVE HOOK

After all refs were updated (or attempted to be updated), if any ref update was successful, and if `$GIT_DIR/hooks/post-receive` file exists and is executable, it will be invoked once with no parameters. The standard input of the hook will be one line for each successfully updated ref:

```
sha1-old SP sha1-new SP refname LF
```

The refname value is relative to `$GIT_DIR`; e.g. for the master head this is "refs/heads/master". The two sha1 values before each refname are the object names for the refname before and after the update. Refs that were created will have sha1-old equal to `0{40}`, while refs that were deleted will have sha1-new equal to `0{40}`, otherwise sha1-old and sha1-new should be valid objects in the repository.

The `GIT_PUSH_CERT*` environment variables can be inspected, just as in pre-receive hook, after accepting a signed push.

Using this hook, it is easy to generate mails describing the updates to the repository.

This example script sends one mail message per ref listing the commits pushed to the repository, and logs the push certificates of signed pushes with good signatures to a logger service:

```
#!/bin/sh

# mail out commit update information.

while read oval nval ref
do
    if expr "$oval" : '0*$' >/dev/null
    then
        echo "Created a new ref, with the following commits:"
        git rev-list --pretty "$nval"
    else
        echo "New commits:"
        git rev-list --pretty "$nval" "^$oval"
    fi |
    mail -s "Changes to ref $ref" commit-list@mydomain
done

# log signed push certificate, if any
```

```

if test -n "${GIT_PUSH_CERT-}" && test ${GIT_PUSH_CERT_STATUS} = G
then
    (
        echo expected nonce is ${GIT_PUSH_NONCE}
        git cat-file blob ${GIT_PUSH_CERT}
    ) | mail -s "push certificate from $GIT_PUSH_CERT_SIGNER" push-log@mydomain
fi
exit 0

```

The exit code from this hook invocation is ignored, however a non-zero exit code will generate an error message.

Note that it is possible for `refname` to not have `sha1-new` when this hook runs. This can easily occur if another user modifies the ref after it was updated by `git-receive-pack`, but before the hook was able to evaluate it. It is recommended that hooks rely on `sha1-new` rather than the current value of `refname`.

POST-UPDATE HOOK

After all other processing, if at least one ref was updated, and if `$GIT_DIR/hooks/post-update` file exists and is executable, then `post-update` will be called with the list of refs that have been updated. This can be used to implement any repository wide cleanup tasks.

The exit code from this hook invocation is ignored; the only thing left for `git-receive-pack` to do at that point is to exit itself anyway.

This hook can be used, for example, to run `git update-server-info` if the repository is packed and is served via a dumb transport.

```

#!/bin/sh
exec git update-server-info

```

QUARANTINE ENVIRONMENT

When `receive-pack` takes in objects, they are placed into a temporary "quarantine" directory within the `$GIT_DIR/objects` directory and migrated into the main object store only after the pre-receive hook has completed. If the push fails before then, the temporary directory is removed entirely.

This has a few user-visible effects and caveats:

1. Pushes which fail due to problems with the incoming pack, missing objects, or due to the pre-receive hook will not leave any on-disk data. This is usually helpful to

prevent repeated failed pushes from filling up your disk, but can make debugging more challenging.

2. Any objects created by the pre-receive hook will be created in the quarantine directory (and migrated only if it succeeds).
3. The pre-receive hook **MUST NOT** update any refs to point to quarantined objects. Other programs accessing the repository will not be able to see the objects (and if the pre-receive hook fails, those refs would become corrupted). For safety, any ref updates from within pre-receive are automatically rejected.

SEE ALSO

[git-send-pack\(1\)](#), [gitnamespaces\(7\)](#)

GIT

Part of the [git\(1\)](#) suite

Git 2.34.1

07/07/2023

[GIT-RECEIVE-PACK\(1\)](#)