



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'gshadow.5'

\$ man gshadow.5

GSHADOW(5) File Formats and Conversions GSHADOW(5)

NAME

gshadow - shadowed group file

DESCRIPTION

/etc/gshadow contains the shadowed information for group accounts.

This file must not be readable by regular users if password security is to be maintained.

Each line of this file contains the following colon-separated fields:

group name

It must be a valid group name, which exist on the system.

encrypted password

Refer to crypt(3) for details on how this string is interpreted.

If the password field contains some string that is not a valid result of crypt(3), for instance ! or *, users will not be able to use a unix password to access the group (but group members do not need the password).

The password is used when a user who is not a member of the group wants to gain the

permissions of this group (see `newgrp(1)`).

This field may be empty, in which case only the group members can gain the group permissions.

A password field which starts with an exclamation mark means that the password is locked. The remaining characters on the line represent the password field before the password was locked.

This password supersedes any password specified in `/etc/group`.

administrators

It must be a comma-separated list of user names.

Administrators can change the password or the members of the group.

Administrators also have the same permissions as the members (see below).

members

It must be a comma-separated list of user names.

Members can access the group without being prompted for a password.

You should use the same list of users as in `/etc/group`.

FILES

`/etc/group`

Group account information.

`/etc/gshadow`

Secure group account information.

gpasswd(5), group(5), grpck(8), grpconv(8), newgrp(1).

shadow-utils 4.8.1

02/06/2024

GSHADOW(5)