



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'htdigest.1'

\$ man htdigest.1

HTDIGEST(1) htdigest HTDIGEST(1)

NAME

htdigest - manage user files for digest authentication

SYNOPSIS

htdigest [-c] passwdfile realm username

SUMMARY

htdigest is used to create and update the flat-files used to store usernames, realm and password for digest authentication of HTTP users. Resources available from the Apache HTTP server can be restricted to just the users listed in the files created by htdigest.

This manual page only lists the command line arguments. For details of the directives necessary to configure digest authentication in httpd see the Apache manual, which is part of the Apache distribution or can be found at <http://httpd.apache.org/>.

OPTIONS

-c Create the passwdfile. If passwdfile already exists, it is deleted first.

passwdfile

Name of the file to contain the username, realm and password. If -c is given, this file is created if it does not already exist, or deleted and recreated if it does exist.

realm The realm name to which the user name belongs. See

<http://tools.ietf.org/html/rfc2617#section-3.2.1> for more details.

username

The user name to create or update in passwdfile. If username does not exist in this file, an entry is added. If it does exist, the password is changed.

SECURITY CONSIDERATIONS

This program is not safe as a setuid executable. Do not make it setuid.

Apache HTTP Server

2018-07-06

HTDIGEST(1)