



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'ibus.1'

\$ man ibus.1

IBUS(1) User Commands IBUS(1)

NAME

ibus - command line utility for ibus

SYNOPSIS

ibus COMMAND [OPTION]...

DESCRIPTION

IBus is an Intelligent Input Bus. It is a new input framework for Linux OS. It provides full featured and user friendly input method user interface. It also may help developers to develop input method easily.

ibus is a command line utility which can restart or exit ibus-daemon, get or set the current ibus engine or list the ibus engines.

Homepage: <https://github.com/ibus/ibus/wiki>

COMMAND

help Show the commands list.

engine [ENGINE_NAME]

Show the current ibus engine when ENGINE_NAME is not given. Set ENGINE_NAME to the current ibus engine.

exit Exit ibus-daemon.

list-engine

Show ibus engines list.

restart

Restart ibus-daemon.

version

Show the ibus version.

`read-cache [--system|--file=FILE]`

Show the content of the user registry cache if `--system` is not given. Show the content of the system registry cache if `--system` is given. Show the content of the custom registry cache `FILE` if `--file=FILE` is given.

`write-cache [--system|--file=FILE]`

Save the user registry cache if `--system` is not given. Save the system registry cache if `--system` is given. Save the custom registry cache `FILE` if `--file=FILE` is given.

By default, it reads the component XML files from the standard component directory (`/usr/share/ibus/component`), you can set `IBUS_COMPONENT_PATH` environment variable for custom component directories, separated by `'|'`.

`address`

Show the D-Bus address of `ibus-daemon`.

`read-config`

Print the setting values in a `gsettings` configuration file.

`reset-config`

Reset the user setting values to the default ones in a `gsettings` configuration file.

`watch` Under construction.

`emoji [--font=FONT|--lang=LANG|--help|--partial-match]`

Launch IBus Emojier (`ibus-emoji (1)`) and save the selected emoji to your clipboard. Can choose an emoji font with `--font` option. Can choose a language of emoji annotations with `--lang` option. If `LANG="en"`, IBus Emojier loads `/usr/share/ibus/dicts/emoji-en.dict` . `--partial-match` option enables to match annotations with a partial string. These settings are available with `ibus-setup (1)` utility.

BUGS

If you find a bug, please report it at <https://github.com/ibus/ibus/issues>

SEE ALSO

`ibus-emoji(7)`