



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'iconv\_close.3'***

**\$ man iconv\_close.3**

ICONV\_CLOSE(3)                      Linux Programmer's Manual                      ICONV\_CLOSE(3)

**NAME**

iconv\_close - deallocate descriptor for character set conversion

**SYNOPSIS**

```
#include <iconv.h>

int iconv_close(iconv_t cd);
```

**DESCRIPTION**

The iconv\_close() function deallocates a conversion descriptor cd previously allocated using iconv\_open(3).

**RETURN VALUE**

When successful, the iconv\_close() function returns 0. In case of error, it sets errno and returns -1.

**VERSIONS**

This function is available in glibc since version 2.1.

**ATTRIBUTES**

For an explanation of the terms used in this section, see attributes(7).

??

?Interface	?Attribute	?Value	?
iconv_close()	Thread safety	MT-Safe	?

??

**CONFORMING TO**

POSIX.1-2001, POSIX.1-2008, SUSv2.

## SEE ALSO

iconv(3), iconv\_open(3)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2017-09-15

ICONV\_CLOSE(3)