



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'inotify_rm_watch.2'

\$ man inotify_rm_watch.2

INOTIFY_RM_WATCH(2) Linux Programmer's Manual INOTIFY_RM_WATCH(2)

NAME

inotify_rm_watch - remove an existing watch from an inotify instance

SYNOPSIS

```
#include <sys/inotify.h>

int inotify_rm_watch(int fd, int wd);
```

DESCRIPTION

inotify_rm_watch() removes the watch associated with the watch descriptor wd from the inotify instance associated with the file descriptor fd.

Removing a watch causes an IN_IGNORED event to be generated for this watch descriptor.

(See inotify(7).)

RETURN VALUE

On success, inotify_rm_watch() returns zero. On error, -1 is returned and errno is set to indicate the cause of the error.

ERRORS

EBADF fd is not a valid file descriptor.

EINVAL The watch descriptor wd is not valid; or fd is not an inotify file descriptor.

VERSIONS

Inotify was merged into the 2.6.13 Linux kernel.

CONFORMING TO

This system call is Linux-specific.

SEE ALSO

inotify_add_watch(2), inotify_init(2), inotify(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2017-09-15

INOTIFY_RM_WATCH(2)