



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'ip-nexthop.8'***

**\$ man ip-nexthop.8**

IP-NEXTHOP(8)                      Linux                      IP-NEXTHOP(8)

#### NAME

ip-nexthop - nexthop object management

#### SYNOPSIS

ip [ ip-OPTIONS ] nexthop { COMMAND | help }

ip nexthop { show | flush } SELECTOR

ip nexthop { add | replace } id ID NH

ip nexthop { get | del } id ID

ip nexthop bucket list BUCKET\_SELECTOR

ip nexthop bucket get id ID index INDEX

SELECTOR := [ id ID ] [ dev DEV ] [ vrf NAME ] [ master DEV ] [ groups ] [ fdb ]

BUCKET\_SELECTOR := SELECTOR | [ nhid ID ]

NH := { blackhole | [ via ADDRESS ] [ dev DEV ] [ onlink ] [ encap ENCAP ] [ fdb ] | group

GROUP [ fdb ] [ type TYPE [ TYPE\_ARGS ] ] }

ENCAP := [ ENCAP\_MPLS ]

ENCAP\_MPLS := mpls [ LABEL ] [ ttl TTL ]

GROUP := id[,weight[/...]]

TYPE := { mpath | resilient }

TYPE\_ARGS := [ RESILIENT\_ARGS ]

RESILIENT\_ARGS := [ buckets BUCKETS ] [ idle\_timer IDLE ] [ unbalanced\_timer UNBALANCED ]

#### DESCRIPTION

ip nexthop is used to manipulate entries in the kernel's nexthop tables.

ip nexthop add id ID

add new nexthop entry

ip nexthop replace id ID

change the configuration of a nexthop or add new one

via [ FAMILY ] ADDRESS

the address of the nexthop router, in the address family FAMILY. Address

family must match address family of nexthop instance.

dev NAME

is the output device.

onlink pretend that the nexthop is directly attached to this link, even if it does

not match any interface prefix.

encap ENCAPTYPE ENCAPHDR

attach tunnel encapsulation attributes to this route.

ENCAPTYPE is a string specifying the supported encapsulation type. Namely:

mpls - encapsulation type MPLS

ENCAPHDR is a set of encapsulation attributes specific to the ENCAPTYPE.

mpls

MPLSLABEL - mpls label stack with labels separated by /

ttl TTL - TTL to use for MPLS header or 0 to inherit from IP

header

group GROUP [ type TYPE [ TYPE\_ARGS ] ]

create a nexthop group. Group specification is id with an optional weight

(id,weight) and a '/' as a separator between entries.

TYPE is a string specifying the nexthop group type. Namely:

mpath - Multipath nexthop group backed by the hash-threshold algo?

rithm. The default when the type is unspecified.

resilient - Resilient nexthop group. Group is resilient to addition

and deletion of nexthops.

TYPE\_ARGS is a set of attributes specific to the TYPE.

resilient

buckets BUCKETS - Number of nexthop buckets. Cannot be changed for  
an existing group

idle\_timer IDLE - Time in seconds in which a nexthop bucket does

not see traffic and is therefore considered idle. Default is 120

seconds

unbalanced\_timer UNBALANCED - Time in seconds in which a nexthop group is unbalanced and is therefore considered unbalanced. The kernel will try to rebalance unbalanced groups, which might result in some flows being reset. A value of 0 means that no rebalancing will take place. Default is 0 seconds

blackhole

create a blackhole nexthop

fdb nexthop and nexthop groups for use with layer-2 fdb entries. A fdb nexthop group can only have fdb nexthops. Example: Used to represent a vxlan remote vtep ip. layer-2 vxlan fdb entry pointing to an ecmp nexthop group containing multiple remote vtep ips.

ip nexthop delete id ID

delete nexthop with given id.

ip nexthop show

show the contents of the nexthop table or the nexthops selected by some criteria.

dev DEV

show the nexthops using the given device.

vrf NAME

show the nexthops using devices associated with the vrf name

master DEV

show the nexthops using devices enslaved to given master device

groups show only nexthop groups

fdb show only fdb nexthops and nexthop groups

ip nexthop flush

flushes nexthops selected by some criteria. Criteria options are the same as show.

ip nexthop get id ID

get a single nexthop by id

ip nexthop bucket show

show the contents of the nexthop bucket table or the nexthop buckets selected by some criteria.

id ID

show the nexthop buckets that belong to a nexthop group with a given id

nhid ID

show the nexthop buckets that hold a nexthop with a given id

dev DEV

show the nexthop buckets using the given device

vrf NAME

show the nexthop buckets using devices associated with the vrf name

master DEV

show the nexthop buckets using devices enslaved to given master device

ip nexthop bucket get id ID index INDEX

get a single nexthop bucket by nexthop group id and bucket index

## EXAMPLES

ip nexthop ls

Show all nexthop entries in the kernel.

ip nexthop add id 1 via 192.168.1.1 dev eth0

Adds an IPv4 nexthop with id 1 using the gateway 192.168.1.1 out device eth0.

ip nexthop add id 2 encap mpls 200/300 via 10.1.1.1 dev eth0

Adds an IPv4 nexthop with mpls encapsulation attributes attached to it.

ip nexthop add id 3 group 1/2

Adds a nexthop with id 3. The nexthop is a group using nexthops with ids 1 and 2 at equal weight.

ip nexthop add id 4 group 1,5/2,11

Adds a nexthop with id 4. The nexthop is a group using nexthops with ids 1 and 2 with nexthop 1 at weight 5 and nexthop 2 at weight 11.

ip nexthop add id 5 via 192.168.1.2 fdb

Adds a fdb nexthop with id 5.

ip nexthop add id 7 group 5/6 fdb

Adds a fdb nexthop group with id 7. A fdb nexthop group can only have fdb nexthops.

ip nexthop add id 10 group 1/2 type resilient buckets 32

Add a resilient nexthop group with id 10 and 32 nexthop buckets.

## SEE ALSO

ip(8)

## AUTHOR

Original Manpage by David Ahern <dsahern@kernel.org>

