



Linux Ubuntu 22.4.5 Manual Pages on command 'jupyter-trust.1'

\$ man jupyter-trust.1

JUPYTER-TRUST(1) User Commands JUPYTER-TRUST(1)

NAME

jupyter-trust - Sign one or more Jupyter notebooks with your key, to trust their dynamic (HTML, Javascript) output

DESCRIPTION

When unsigned, you have to re-execute the notebook to see output.

OPTIONS

Arguments that take values are actually convenience aliases to full Configurables, whose aliases are listed on the help line. For more information on full configurables, see '--help-all'.

--reset

Delete the trusted notebook cache. All previously signed notebooks will become untrusted.

--debug

set log level to logging.DEBUG (maximize logging output)

-y

Answer yes to any questions instead of prompting.

--generate-config

generate default config file

--config=<Unicode> (JupyterApp.config_file)

Default: u" Full path of a config file.

--log-level=<Enum> (Application.log_level)

Default: 30 Choices: (0, 10, 20, 30, 40, 50, 'DEBUG', 'INFO', 'WARN', 'ER?

ROR', 'CRITICAL') Set the log level by value or name.

To see all available configurables, use `--help-all`

EXAMPLES

```
jupyter trust mynotebook.ipynb and_this_one.ipynb
```

jupyter-trust

September 2015

JUPYTER-TRUST(1)