



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'logsave.8'***

#### ***\$ man logsave.8***

LOGSAVE(8)                      System Manager's Manual                      LOGSAVE(8)

#### NAME

logsave - save the output of a command in a logfile

#### SYNOPSIS

logsave [ -asv ] logfile cmd\_prog [ ... ]

#### DESCRIPTION

The logsave program will execute cmd\_prog with the specified argument(s), and save a copy of its output to logfile. If the containing directory for logfile does not exist, logsave will accumulate the output in memory until it can be written out. A copy of the output will also be written to standard output.

If cmd\_prog is a single hyphen ('-'), then instead of executing a program, logsave will take its input from standard input and save it in logfile

logsave is useful for saving the output of initial boot scripts until the /var partition is mounted, so the output can be written to /var/log.

#### OPTIONS

- a This option will cause the output to be appended to logfile, instead of replacing its current contents.
- s This option will cause logsave to skip writing to the log file text which is bracketed with a control-A (ASCII 001 or Start of Header) and control-B (ASCII 002 or Start of Text). This allows progress bar information to be visible to the user on the console, while not being written to the log file.
- v This option will make logsave to be more verbose in its output to the user.

#### AUTHOR

Theodore Ts'o (tytso@mit.edu)

SEE ALSO

fsck(8)

E2fsprogs version 1.46.5

December 2021

LOGSAVE(8)