

Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

nime.types.5'

Rocky Enterprise Linux 9.2 Manual Pages on command 'n			
\$ man mime.types.5			
mime.t	ypes(5)	OpenPrinting	mime.types(5)
NAME			
mi	me.types - mime type de	escription file for cups	
DESC	RIPTION		
Th	The mime.types file defines the recognized file types.		
Ac	Additional file types are specified in files with the extension .types in the CUPS config?		
ur	ation directory.		
Ea	Each line in the mime.types file is a comment, blank, or rule line. Comment lines start		
wi	with the # character. Rule lines start with the MIME media type and are optionally fol?		
lov	wed by a series of file rec	cognition rules:	
	mime/type [rule rule]		
Б.			a baadaalaab ahayaatay (V)
KI	dies can be extended ove	er multiple lines using th	e backslash character (\):
	mime/type [really-really-	really-long-rule \	
	rule]	, . 3	
	1		

ascending alphanumeric order for the purposes of matching. See the "TYPE MATCHING AND PRIORITY" section for more information.

The rules may be grouped using parenthesis, joined using "+" for a logical AND, joined us? ing "," or whitespace for a logical OR, and negated using "!".

RULES

Rules take two forms - a filename extension by itself and functions with test values in? side parenthesis. The following functions are available:

match("pattern")

True if the filename matches the given shell wildcard pattern.

ascii(offset,length)

True if the length bytes starting at offset are valid printable ASCII (CR, NL, TAB, BS, 32-126).

printable(offset,length)

True if the length bytes starting at offset are printable 8-bit chars (CR, NL, TAB, BS, 32-126, 128-254).

priority(number)

Specifies the relative priority of this MIME media type. The default priority is 100. Larger values have higher priority while smaller values have lower priority.

string(offset, "string")

True if the bytes starting at offset are identical to string.

istring(offset,"string")

True if the bytes starting at offset match string without respect to case.

char(offset,value)

True if the byte at offset is identical to value.

short(offset,value)

True if the 16-bit big-endian integer at offset is identical to value.

int(offset,value)

True if the 32-bit big-endian integer at offset is identical to value.

locale("string")

True if current locale matches string.

contains(offset,range,"string")

True if the bytes starting at offset for range bytes contains string.

STRING CONSTANTS

String constants can be specified inside quotes ("") for strings containing whitespace and angle brackets (<>) for hexadecimal strings.

TYPE MATCHING AND PRIORITY

When CUPS needs to determine the MIME media type of a given file, it checks every MIME me? dia type defined in the .types files. When two or more types match a given file, the type chosen will depend on the type name and priority, with higher-priority types being used over lower-priority ones. If the types have the same priority, the type names are sorted alphanumerically in ascending order and the first type is chosen.

For example, if two types "text/bar" and "text/foo" are defined as matching the extension "doc", normally the type "text/bar" will be chosen since its name is alphanumerically smaller than "text/foo". However, if "text/foo" also defines a higher priority than "text/bar", "text/foo" will be chosen instead.

FILES

/etc/cups - Typical CUPS configuration directory.

EXAMPLES Page 3/4

Define two MIME media types for raster data, with one being a subset with higher priority:

string(0,"RaS3") string(0,"3SaR")

image/pwg-raster string(0,"RaS2") + \

string(4,PwgRaster<00>) priority(150)

SEE ALSO

cups-files.conf(5), cupsd.conf(5), cupsd(8), cupsfilter(8), mime.convs(5), CUPS Online Help (http://localhost:631/help)

COPYRIGHT

Copyright ? 2021-2022 by OpenPrinting.

2021-02-28 CUPS mime.types(5)