



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'mkdir.1'

\$ man mkdir.1

MKDIR(1) User Commands MKDIR(1)

NAME

mkdir - make directories

SYNOPSIS

mkdir [OPTION]... DIRECTORY...

DESCRIPTION

Create the DIRECTORY(ies), if they do not already exist.

Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE

set file mode (as in chmod), not a=rwx - umask

-p, --parents

no error if existing, make parent directories as needed

-v, --verbose

print a message for each created directory

-Z set SELinux security context of each created directory to the default type

--context[=CTX]

like **-Z**, or if CTX is specified then set the SELinux or SMACK security context to

CTX

--help display this help and exit

--version

output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2020 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

`mkdir(2)`

Full documentation <<https://www.gnu.org/software/coreutils/mkdir>>

or available locally via: `info '(coreutils) mkdir invocation'`

GNU coreutils 8.32

February 2024

MKDIR(1)