



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'mq_close.3'

\$ man mq_close.3

MQ_CLOSE(3) Linux Programmer's Manual MQ_CLOSE(3)

NAME

mq_close - close a message queue descriptor

SYNOPSIS

```
#include <mqueue.h>

int mq_close(mqd_t mqdes);

Link with -lrt.
```

DESCRIPTION

mq_close() closes the message queue descriptor mqdes.

If the calling process has attached a notification request (see (mq_notify(3))) to this message queue via mqdes, then this request is removed, and another process can now attach a notification request.

RETURN VALUE

On success mq_close() returns 0; on error, -1 is returned, with errno set to indicate the error.

ERRORS

EBADF The message queue descriptor specified in mqdes is invalid.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

```
????????????????????????????????????????????????????????
?Interface ? Attribute ? Value ?
????????????????????????????????????????????????????????
?mq_close() ? Thread safety ? MT-Safe ?
```

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

NOTES

All open message queues are automatically closed on process termination, or upon `exece(2)`.

SEE ALSO

`mq_getattr(3)`, `mq_notify(3)`, `mq_open(3)`, `mq_receive(3)`, `mq_send(3)`, `mq_unlink(3)`, `mq_overview(7)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-08-13

MQ_CLOSE(3)