



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'mq_unlink.2'

\$ man mq_unlink.2

MQ_UNLINK(3) Linux Programmer's Manual MQ_UNLINK(3)

NAME

mq_unlink - remove a message queue

SYNOPSIS

```
#include <mqueue.h>

int mq_unlink(const char *name);

Link with -lrt.
```

DESCRIPTION

mq_unlink() removes the specified message queue name. The message queue name is removed immediately. The queue itself is destroyed once any other processes that have the queue open close their descriptors referring to the queue.

RETURN VALUE

On success mq_unlink() returns 0; on error, -1 is returned, with errno set to indicate the error.

ERRORS

- EACCES The caller does not have permission to unlink this message queue.
- ENAMETOOLONG name was too long.
- ENOENT There is no message queue with the given name.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?mq_unlink() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008.

SEE ALSO

mq_close(3), mq_getattr(3), mq_notify(3), mq_open(3), mq_receive(3), mq_send(3), mq_over?
view(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-08-13

MQ_UNLINK(3)