

# Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

## Rocky Enterprise Linux 9.2 Manual Pages on command 'netconfig.5'

#### \$ man netconfig.5

NETCONFIG(5)

BSD File Formats Manual

NETCONFIG(5)

NAME

netconfig ? network configuration data base

#### SYNOPSIS

/etc/netconfig

#### DESCRIPTION

The netconfig file defines a list of ?transport names?, describing their semantics and pro?

tocol. In FreeBSD, this file is only used by the RPC library code.

Entries have the following format:

network\_id semantics flags family protoname device libraries

Entries consist of the following fields:

network\_id The name of the transport described.

semantics Describes the semantics of the transport. This can be one of:

tpi\_clts Connectionless transport.

tpi\_cots Connection-oriented transport

tpi\_cots\_ord Connection-oriented, ordered transport.

tpi\_raw A raw connection.

flags This field is either blank (specified by ?-?), or contains a ?v?, meaning visi?

ble to the getnetconfig(3) function.

family The protocol family of the transport. This is currently one of:

inet6 The IPv6 (PF\_INET6) family of protocols.

inet The IPv4 (PF\_INET) family of protocols.

loopback The PF\_LOCAL protocol family.

protoname The name of the protocol used for this transport. Can currently be either udp,

tcp or empty.

device This field is always empty in FreeBSD.

libraries This field is always empty in FreeBSD.

The order of entries in this file will determine which transport will be preferred by the

RPC library code, given a match on a specified network type. For example, if a sample net? work config file would look like this:

udp6	tpi_clts v inet6 udp
tcp6	tpi_cots_ord v inet6 tcp
udp	tpi_clts v inet udp
tcp	tpi_cots_ord v inet tcp
rawip	tpi_raw - inet
local	tpi_cots_ord - loopback

then using the network type udp in calls to the RPC library function (see rpc(3)) will make the code first try udp6, and then udp.

getnetconfig(3) and associated functions will parse this file and return structures of the

following format:

#### struct netconfig {

char \*nc\_netid; /\* Network ID \*/ unsigned long nc\_semantics; /\* Semantics (see below) \*/ unsigned long nc\_flag; /\* Flags (see below) \*/ char \*nc\_protofmly; /\* Protocol family \*/ char \*nc\_proto; /\* Protocol name \*/ char \*nc\_device; /\* Network device pathname (unused) \*/ unsigned long nc\_nlookups; /\* Number of lookup libs (unused) \*/ char \*\*nc\_lookups; /\* Names of the libraries (unused) \*/

### };

FILES

/etc/netconfig

#### SEE ALSO

getnetconfig(3), getnetpath(3)