



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

***Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-explore.1'***

***\$ man npm-explore.1***

NPM-EXPLORE(1)

NPM-EXPLORE(1)

NAME

npm-explore - Browse an installed package

Synopsis

npm explore <pkg> [ -- <command> ]

Note: This command is unaware of workspaces.

Description

Spawn a subshell in the directory of the installed package specified.

If a command is specified, then it is run in the subshell, which then immediately terminates.

This is particularly handy in the case of git submodules in the node\_modules folder:

npm explore some-dependency -- git pull origin master

Note that the package is not automatically rebuilt afterwards, so be sure to use npm rebuild <pkg> if you make any changes.

Configuration

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->
```

shell

? Default: SHELL environment variable, or "bash" on Posix, or "cmd.exe" on Windows

? Type: String

The shell to run for the npm explore command. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->
```

## See Also

? npm help folders

? npm help edit

? npm help rebuild

? npm help install

undefined NaN

NPM-EXPLORE(1)