



**Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!**

### ***Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-prefix.1'***

**\$ man npm-prefix.1**

NPM-PREFIX(1)

NPM-PREFIX(1)

NAME

npm-prefix - Display prefix

Synopsis

npm prefix [-g]

Note: This command is unaware of workspaces.

Description

Print the local prefix to standard output. This is the closest parent directory to contain a package.json file or node\_modules directory, unless -g is also specified.

If -g is specified, this will be the value of the global prefix. See npm help config for more detail.

Example

npm prefix

/usr/local/projects/foo

npm prefix -g

/usr/local

Configuration

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

global

? Default: false

? Type: Boolean

Operates in "global" mode, so that packages are installed into the prefix folder instead

of the current working directory. See npm help folders for more on the differences in behavior.

? packages are installed into the {prefix}/lib/node\_modules folder, instead of the current working directory.

? bin files are linked to {prefix}/bin

? man pages are linked to {prefix}/share/man

<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

#### See Also

? npm help root

? npm help bin

? npm help folders

? npm help config

? npm help npmrc

undefined NaN

NPM-PREFIX(1)