



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-repo.1'

\$ man npm-repo.1

NPM-REPO(1)

NPM-REPO(1)

NAME

npm-repo - Open package repository page in the browser

Synopsis

npm repo [<pkgname> [<pkgname> ...]]

Description

This command tries to guess at the likely location of a package's repository URL, and then tries to open it using the --browser config param. If no package name is provided, it will search for a package.json in the current folder and use the repository property.

Configuration

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

browser

? Default: OS X: "open", Windows: "start", Others: "xdg-open"

? Type: null, Boolean, or String

The browser that is called by npm commands to open websites.

Set to false to suppress browser behavior and instead print urls to terminal.

Set to true to use default system URL opener. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

workspace

? Default:

? Type: String (can be set multiple times)

Enable running a command in the context of the configured workspaces of the current

project while filtering by running only the workspaces defined by this configuration option.

Valid values for the workspace config are either:

? Workspace names

? Path to a workspace directory

? Path to a parent workspace directory (will result in selecting all workspaces within that folder)

When set for the npm init command, this may be set to the folder of a workspace which does not yet exist, to create the folder and set it up as a brand new workspace within the project.

This value is not exported to the environment for child processes. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

workspaces

? Default: null

? Type: null or Boolean

Set to true to run the command in the context of all configured workspaces.

Explicitly setting this to false will cause commands like install to ignore workspaces altogether. When not set explicitly:

? Commands that operate on the node_modules tree (install, update, etc.) will link workspaces into the node_modules folder. - Commands that do other things (test, exec, publish, etc.) will operate on the root project, unless one or more workspaces are specified in the workspace config.

This value is not exported to the environment for child processes. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

include-workspace-root

? Default: false

? Type: Boolean

Include the workspace root when workspaces are enabled for a command.

When false, specifying individual workspaces via the workspace config, or all workspaces via the workspaces flag, will cause npm to operate only on the specified workspaces, and not on the root project. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? npm help docs

? npm help config

undefined NaN

NPM-REPO(1)