



Full credit is given to the above companies including the Operating System (OS) that this PDF file was generated!

Rocky Enterprise Linux 9.2 Manual Pages on command 'npm-root.1'

\$ man npm-root.1

NPM-ROOT(1)

NPM-ROOT(1)

NAME

npm-root - Display npm root

Synopsis

npm root [-g]

Description

Print the effective node_modules folder to standard out.

Useful for using npm in shell scripts that do things with the node_modules folder. For

example:

```
#!/bin/bash
```

```
global_node_modules="$(npm root --global)"
```

```
echo "Global packages installed in: ${global_node_modules}"
```

Configuration

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit  
manually --> <!-- see lib/utils/config/definitions.js -->
```

global

? Default: false

? Type: Boolean

Operates in "global" mode, so that packages are installed into the prefix folder instead of the current working directory. See npm help folders for more on the differences in behavior.

? packages are installed into the {prefix}/lib/node_modules folder, instead of the current working directory.

? bin files are linked to {prefix}/bin

? man pages are linked to {prefix}/share/man

<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/defini?
tions.js -->

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

? npm help prefix

? npm help bin

? npm help folders

? npm help config

? npm help npmrc

undefined NaN

NPM-ROOT(1)